

800

SPRING REWIND REELS

To handle 3/4" or 1" I.D. hose.



Standard Configuration Shown

- Rollformed channel frame for heavy-duty applications.
- Non sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlet 90° balanced pressure swivel joint 1" female NPT threads.
- Standard outlet 1" female NPT threads.
- Pressures to 1000 psi (69 bar).
- Temperatures from -40° F to +250° F (-40° C to +121° C).
- Consult factory for other pressures & temps.
- 4-way roller assembly.
- Constant Tension is available – consult factory.

For:

- Fuel Dispensing (Consult Factory)
- Waste Oil Evacuation
- Air/Water

Model Number	Hose Capacity			Approx. Weight		Standard Roller Assy	Reel Dimensions***									
	I.D. (in)	3/4"	1"	NET	SHIP		A	B	C	D	E	F	G	H	X	Y
	I.D. (mm)	19	25													
	O.D. (in)	1-9/32"	1-9/16"													
	O.D. (mm)	33	40													
816-25-26B	60	35	96	131	R204	9.25	4	10.5	25	26.12	13.5	25.88	13.5	4.5	22	
	18	11	44	59		235	102	267	635	663	343	657	343	114	559	
818-25-26B	70	50	102	137	R206	11.25	6	10.5	25	26.12	15.5	25.88	13.5	6.5	22	
	21	15	46	62		286	152	267	635	663	394	657	343	165	559	
820-25-26-10.5A	85	75	131	166	R308	13.25	8	10.5	25	27	18.25	25.88	13.5	8.5	22	
	26	23	59	75		337	203	267	635	686	464	657	343	216	559	
820-30-31-10.5A	-	100	137	172	R308	13.25	8	10.5	28.5	30.5	18.25	31.38	17	8.5	25.5	
	-	30	62	78		337	203	267	724	775	464	797	432	216	648	
820-30-31-15.5A	100	-	145	180	R308	13.25	8	15.5	28.5	30.5	18.25	31.38	17	8.5	25.5	
	30	-	66	82		337	203	394	724	775	464	797	432	216	648	

Notes:

1. Specifications subject to change.
2. Reels models and capacities shown are for standard drag applications; for vertical lift applications consult factory.
3. Other sizes, from standard components, available on request.
4. For a detailed parts breakdown drawing, request ISO 42.
5. **Finish:** refer to Page 4.
6. **Be sure to check dimensions and weights prior to ordering.**

NOTICE: A Flexible Connector must be used between the inlet pipe and the inlet swivel joint.

* When shipped as a parcel package (via Fed-Ex or UPS Ground).

*** x,y indicate mounting holes. See page 2

