

N500



Standard Configuration Shown

For:

- Chassis Grease
- Hydraulics
- Air/Water

Model Number	Hose Capacity of Reel			Approx. Weight		Standard Roller Assy	Reel Dimensions***			
	feet			lb.			C	E	G	H
	m.			kg.						
I.D. (in) I.D. (mm)	1/4" 6	3/8" 10	NET	Frt. SHIP Wt.						
O.D. (in) O.D. (mm)	5/8" 16	3/4" 19								
N515-14-16-8C	25 8	25 8	48* 22	83 38	N203	8 203	17.62 448	16.25 413	9.12 232	
N515-16-17C	35 11	35 11	51* 23	86 39	N203	10.5 267	18.5 470	17 432	9.12 232	
N515-19-20J	50 15	50 15	63* 29	98 44	N203	10.5 267	20.75 527	20 508	10.62 270	
N515-23-24J	75 23	75 23	75* 34	110 50	N203	15.5 394	23.75 603	24 610	12.62 321	

Notes:

1. Specifications subject to change.
2. Reel models and capacities shown are for standard drag applications; for vertical lift applications consult factory.
3. Other sizes, from standard components, available on request.
4. For a detailed parts breakdown drawing, request ISO 92.
5. **Finish:** refer to Page 4.
6. **Be sure to check dimensions and weights prior to ordering.**

NOTICE: A Flexible Connector must be used between the inlet pipe and the inlet swivel joint.

* When shipped as a parcel package (via Fed-Ex or UPS Ground), Net wt. plus carton wt.

*** x,y indicate mounting holes. See page 2

