

# N800

## SPRING REWIND REELS

To handle 3/4" or 1" I.D. hose.

- Standard N series has a narrow frame and compact mounting base.
- Non sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlet 90° balanced pressure swivel joint 1" female NPT threads.
- Standard outlet 1" female NPT threads.
- Pressures to 1000 psi (69 bar).
- Temperatures from -40° F to +250° F (-40° C to +121° C).
- Consult factory for other pressures & temps.
- 4-way roller assembly
- Constant Tension is available – consult factory.



Optional TR roller position shown

For:

- Fuel Dispensing  
(Consult Factory)

- Waste Oil Evacuation
- Air/Water

Model Number	Hose Capacity			Approx. Weight		Standard Roller Assy	Reel Dimensions***							
	feet			lb.			in.							
	m.			kg.			mm							
	I.D. (in) I.D. (mm)	3/4" 19	1" 25	NET	SHIP		A	B	C	E	F	G	H	X
	O.D. (in) O.D. (mm)	1-9/32" 33	1-9/16" 40											
N816-19-20J		25 8	15 5	75 34	91* 41	N204	10 254	4 102	10.5 267	20.75 527	13 330	20 508	10.62 270	8 203
N818-23-24J		50 15	25 8	87 39	100 45	N206	12 305	6 152	10.5 267	23.75 603	15 381	24 610	12.62 321	10 254
N816-25-26B		60 18	35 11	96 44	131 59	N204	10 254	4 102	10.5 267	25.25 641	13 330	26 660	13.62 346	8 203
N818-25-26B		70 21	50 15	102 46	137 62	N206	12 305	6 152	10.5 267	25.25 641	15 381	26 660	13.62 346	10 254

**Notes:**

1. Specifications subject to change.
2. Reels models and capacities shown are for standard drag applications; for vertical lift applications consult factory.
3. Other sizes, from standard components, available on request.
4. For a detailed parts breakdown drawing, request ISO 81.
5. **Finish:** refer to Page 4.

**6. Be sure to check dimensions and weights prior to ordering.**

**NOTICE:** A Flexible Connector must be used between the inlet pipe and the inlet swivel joint.

\* When shipped as a parcel package (via Fed-Ex or UPS Ground).

\*\*\* x,y indicate mounting holes. See page 2

