

N800

SPRING REWIND REELS

To handle 3/4" or 1" I.D. hose.

- Standard N series has a narrow frame and compact mounting base
- Non sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlet 90° balanced pressure swivel joint 1" female NPT threads.
- Standard outlet 1" female NPT threads.
- Pressures to 1000 psi (69 bar).
- Temperatures from -40° F to +250° F (-40° C to +121° C).
- Consult factory for other pressures & temps.
- 4-way roller assembly
- Constant Tension is available – consult factory.



Optional TR roller position shown

- For:
- Fuel Dispensing
 - Air/Water
 - Waste Oil Evacuation

Model Number	Hose Capacity			Approx. Weight		Standard Roller Assy	Dimensions***				
	feet			NET	SHIP		C	E	F	G	X
	m.										
	I.D. (in)	3/4"	1"								
	I.D. (mm)	19	25								
	O.D. (in)	1-9/32"	1-9/16"								
	O.D. (mm)	33	40								
N816-19-20J		25	15	75	91*	N204	10.5	20.75	13	20	8
		8	5	34	41		267	527	330	508	203
N818-23-24J		50	25	87	100	N206	10.5	23.75	15	24	10
		15	8	39	45		267	603	381	610	254
N816-25-26B		60	35	96	131	N204	10.5	25.25	13	26	8
		18	11	44	59		267	641	330	660	203
N818-25-26B		70	50	102	137	N206	10.5	25.25	15	26	10
		21	15	46	62		267	641	381	660	254

Notes:

1. Specifications subject to change.
2. Reels models and capacities shown are for standard drag applications; for vertical lift applications consult factory.
3. Other sizes, from standard components, available on request.
4. For a detailed parts breakdown drawing, request ISO 81.
5. **Finish:** refer to Page 4.

6. Be sure to check dimensions and weights prior to ordering.

NOTICE: A Flexible Connector must be used between the inlet pipe and the inlet swivel joint.

* When shipped as a parcel package (via Fed-Ex or UPS Ground).

*** x,y indicate mounting holes. See page 2

