

1000



Standard Configuration Shown

COMPACT MANUAL REWIND REELS

To handle single 1/4" or 3/8" I.D. hose.

- Lightweight
- Compact
- Direct crank rewind permanently attached.
- Adjustable cam lock brake standard.
- Optional pin lock available.
- Standard inlet 90° ball bearing swivel joint 1/2" female NPT threads.
- Standard outlet 3/8" female NPT threads.
- Pressures to 3000 psi (207 bar).
- Temperatures from +20° F to +400° F (-7° C to +204° C).
- Consult factory for other pressures & temps.

For:

- Pressure Washing
- Washdown
- Spray Operations
- Air

Model Number	Hose Capacity of Reel			Approx. Weight		Reel Dimensions***	
	I.D. (in) I.D. (mm)	feet m.		lb. kg.		inches mm.	
	1/4" 6	100	75	23	30*	F	X
	3/8" 10	150	100	24	30*		
	5/8" 16	275	175	25	30*		
	3/4" 19			NET	SHIP		
1014-14-16		31	23	10	14	19 483	4 102
1016-14-16		46	31	11	14	21 533	6 152
1020-14-16		84	53	11	14	25 635	10 254

Notes:

1. Specifications subject to change.
2. Other sizes, from standard components, available on request.
3. For a detailed parts breakdown drawing, request ISO 165.
4. **Finish:** refer to Page 4.

5. Be sure to check dimensions and weights prior to ordering.

NOTICE: A Flexible Connector must be used between the inlet pipe and the inlet swivel joint.

* When shipped as a parcel package (via Fed-Ex or UPS Ground).

*** x,y indicate mounting holes. See page 2

