

# N800

## SPRING REWIND REELS

To handle 3/4" or 1" I.D. hose.

- Standard N series has a narrow frame and compact mounting base
- Non sparking ratchet assembly.
- Declutching arbor to prevent damage from reverse winding.
- Standard inlet 90° balanced pressure swivel joint 1" female NPT threads.
- Standard outlet 1" female NPT threads.
- Pressures to 1000 psi (69 bar).
- Temperatures from -40° F to +250° F (-40° C to +121° C).
- Consult factory for other pressures & temps.
- 4-way roller assembly
- Constant Tension is available – consult factory.



Optional TR roller position shown

For:

- Fuel Dispensing
- Waste Oil Evacuation
- Air/Water

Model Number	Hose Capacity			Approx. Weight		Standard Roller Assy	Dimensions***				
	feet			NET	SHIP		C	E	F	G	X
	m.										
I.D. (in) I.D. (mm)	3/4" 19	1" 25	kg.		mm		mm		mm		
O.D. (in) O.D. (mm)	1-9/32" 33	1-9/16" 40									
N816-19-20J	25 8	15 5	75 34	91* 41	N204	10.5 267	20.75 527	13 330	20 508	8 203	
N818-23-24J	50 15	25 8	87 39	100 45	N206	10.5 267	23.75 603	15 381	24 610	10 254	
N816-25-26B	60 18	35 11	96 44	131 59	N204	10.5 267	25.25 641	13 330	26 660	8 203	
N818-25-26B	70 21	50 15	102 46	137 62	N206	10.5 267	25.25 641	15 381	26 660	10 254	

**Notes:**

1. Specifications subject to change.
2. Reels models and capacities shown are for standard drag applications; for vertical lift applications consult factory.
3. Other sizes, from standard components, available on request.
4. For a detailed parts breakdown drawing, request ISO 81.
5. **Finish:** refer to Page 4.

**6. Be sure to check dimensions and weights prior to ordering.**

**NOTICE:** A Flexible Connector must be used between the inlet pipe and the inlet swivel joint.

\* When shipped as a parcel package (via Fed-Ex or UPS Ground).

\*\*\* x,y indicate mounting holes. See page 2

